

DEVICE FOR PRESSURE CLEARING OF PASSAGEWAYS

5 TECHNICAL FIELD OF THE INVENTION

The present invention relates to maintenance of mechanical systems employing pressure passages. More specifically the invention is a device for clearing and cleaning water passages, hydraulic and pneumatic passageways in technical gear and infrastructure.

10

BACKGROUND OF THE INVENTION

Mechanical devices employing pneumatic or hydraulic parts utilize pressurized gases or liquids for affecting force and torque on working objects. The pressurized gases or liquids activate linear or rotational gear that exerts a mechanical effect on the target objects. Such equipment as for example presses, grinders, cutters and mills require free passage of the liquids, as the mechanical design dictates, in order to effectively run the equipment in specified conditions. Some other technical applications are not involved in mechanical reforming of objects, but rather employ non pressurized or slightly pressurized redirection of fluids, such are typically draining systems such as air conditioning, irrigation and sewage.

A major tool in the dentist's art is a set of hand –pieces used for drilling, cleaning and treating the teeth and gums of the patient. Air driven drilling hand –pieces typically contain an air driven turbine which drives the drill bit that drills into the tooth or bone. The hand -piece that is held by the dentist during drilling
5 or otherwise treating of a patient. Typically, a dentist stores several hand –pieces which are easily interchangeable due to a quick release connection. The debris formed in the operation of the drill is driven away from the drilling site by a jet of water aimed at the site of drilling. The water jet also cools the teeth and drill in the course of treatment, preventing heat damages affecting the tooth. The
10 water passages in the hand – piece are susceptible of blockage by precipitated salts, and organic matter. The connectors, also known as couplers, that connect the hand piece to the tubing of the treatment unit are also susceptible of blockage in their water passages.

Since water passages obstructions are harmful in respect of the fact
15 that they prevent cooling and debris removal in the course of drilling, and hinder achieving proper sterilization of the hand – piece, periodic or ad hoc treatments of the water passages of the hand – pieces and coupler are implemented.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1A is a schematic side view of a clearing device of the invention;

Fig. 1B is a schematic side view of a clearing device of the invention in which a tightening member is shown screwed on the piston, showing a part of
5 the thread enveloping the cylinder;

Fig. 2 is a schematic sectional view of a clearing device of the invention showing fluid driving mechanism;

Fig. 3A is a schematic isometric view of a flushing device of the invention without a tightening member at a position prior to coupling to a dentist's
10 hand – piece;

Fig. 3B is a schematic isometric view of a flushing device of the invention without a tightening member, coupled to a dentist's hand – piece.

DETAILED DESCRIPTION OF THE PRESENT INVENTION

The embodiments of the present invention are pressurizing devices for clearing passageways of gasses or liquids by building up pressure that clears the obstructed passageway. The pressure provided by the device of the invention may be used in conjunction with an auxiliary clearing agent, such as cleansing liquid or a solvent, or a gas.

A specific implementation of the device of the invention is in the clearing of the water passages of a hand – piece of a dentist. The instruments are cleared periodically, or on demand, by pressurizing cleansing liquid through them. In order to flush a hand – piece, it is detached from the treatment unit. A clearing device of the invention is connected to the hand – piece by its coupler, typically a Midwest 6 – hole coupler. A flushing device of the invention is described schematically in **Figs 1A** and **1B** to which reference is now made. In **Fig. 1A** a flushing device of the invention generally designated **20** contains a piston **22** inserted in cylinder **24**. In a preferred embodiment of the present invention the cylinder bears at least on a part of its outer surface a screw thread **26**. At the right end of cylinder **24** is connected a coupler **28**. Functionally, piston **22** can move in the direction of double headed arrow **30**. As the piston moves inside cylinder **25**, it pressurizes a clearing liquid inside this cylinder, which can then effectively clear water passages in a hand – piece (not shown), connected to coupler **28**.

In **Fig. 1B** another feature of the present invention is described. A tightening member **40**, is a typically a cylindrical component having an internal screw thread (not shown) that fits with the external screw thread **26**. By turning

the tightening member **40** in one direction, the piston **22** is pressed inside the cylinder **26**. As the cylinder is pushed into the cylinder, the clearing fluid stored in the cylinder is pressurized out of the cylinder into the coupler **28** and to the hand - piece (not shown). The mechanism for driving of the cleansing fluid into the hand - piece is described in reference to **Fig. 2**. Piston **50** pushes into cylinder **52**, pressing the liquid in the cylinder. A gasket **54** prevents the backflow of the fluid in the direction of the piston. Fluid channel **56** traversing the coupler **58** transfers pressurized cleansing liquid into the hand - piece, or to a coupler, or to an adapter thereof (not shown). The hand piece is connected by screwing to internal screw thread **60**, directly or by an adaptor.

A schematic isometric view of a flushing device of the invention is shown in **Fig. 3A** to which reference is now made. The flushing device **80**, which is shown without a tightening member is shown such that its coupler **82** faces a hand piece **84** having an external screw thread **86** of it coupler at its coupling end. In **Fig. 3B** the flushing device **80** is shown connected to the hand - piece **84**. Piston **88** is now ready to be pushed in the direction of arrow **90**, for cleansing the water passages of the hand - piece.

In another embodiment of the invention, the piston is outwardly screw - threaded such that the tightening is effected by turning the piston against a complementary screw thread associated with a part of the inner face of the cylinder.

The implementations of the invention are in maintaining various types of appliances in which gas and liquid passages are to be kept clear of obstructions. Referring to **Figs 1A** and **1B**, the coupler **28** is used for connecting

the device of the invention to the treated devices. For pressure coupling, or for other coupling, the coupler is threaded on the inside or on the outside or both, using a standard thread of the art. However any kind of intermediate coupling can be used to connect the appliance to be maintained with the pressure building
5 device of the invention. The piston may be used to pressurize a liquid, such as water or acid, or a gas such as air or inert gas.

Uses for the pressurizing device of the invention are in various technical field. Vehicle maintenance uses are for clearing fuel passageways, cooling water passageways and water sprinklers. In the printing field, use is for
10 cleaning ink passageways and for inkjets and nozzles. For medical appliances the system of the invention is used for clearing fluid passageways. Obstructions to pneumatic gear using pressurized liquid for powering mechanical equipment, can be cleared using the system of the invention by applying pressurized clearing gas or liquids. In air conditioning, clogged drainage passageways can
15 be cleared by using the system of the invention. Likewise, water installations and sewage system can use the system of the invention for clearing clogs. As mentioned above, the system of the invention can be used for clearing passageways of non pressurized or slightly pressurised flow of liquids such as in oil channels in mechanical appliances.

20

The system of the invention may be manufactured from metal or from plastic parts, or from any other suitable material which may withstand pressure and chemical effect of the clearing agent.